

TORMACH® 1100M®

TRAVELS

X-Axis	18 in. (457 mm)
Y-Axis	11 in. (279 mm)
Z-Axis	16.25 in. (413 mm)

SPINDLE

Spindle Power	2 hp (1.49 kW)
Maximum Speed	7500 RPM
Transmission	Poly-V Belt
Spindle Taper	R8
Thread Machining	<ul style="list-style-type: none"> • Tension/Compression • Auto-Reversing • Thread Mill

MAXIMUM FEED RATE

X- and Y-Axis	110 IPM (2.79 m/min)
Z-Axis	90 IPM (2.29 m/min)

POWER

Power Required	Single-Phase 230 Vac, 50/60 Hz, 20A breaker
----------------	---

MACHINE SPECIFICATIONS

Table Size	34 in. × 9.5 in. (863 mm × 241 mm)
Table Slots	5/8 in. (15.9 mm) (three slots)
Spindle Nose to Table Max Clearance	17 in. (432 mm)
Spindle Centerline to Machine Column	11 in. (279 mm)
Typical System Footprint	69 in. × 56.5 in. (1753 mm × 1435 mm)
Overall System Height	96 in. (2439 mm)
Typical System Weight	1600 lb (726 kg)

FRAME

Frame and Table	Cast iron frame and table, with hand-scraped hydrodynamic ways and tapered adjustment gibs
Way Surfaces	Low-friction PTFE-filled, Acetyl-bonded sliding surface. Similar to Rulon® and Turcite®.



OPTIONAL ACCESSORIES

Automatic Tool Changer
Power Drawbar
4th Axis
SmartCool™ Coolant System
RapidTurn™ Chucker Lathe Accessory
Full Enclosure
High-Speed Spindle

MACHINE CONTROLLER

POWERED BY
PathPilot®
A Better User Experience

PathPilot® HUB

PathPilot HUB is a browser-based, full-featured PathPilot simulator, producing usable G-Code.

User-friendly design
Support for up to 4-axis continuous machining
Intuitive conversational programming
Usable G-Code Memory: Brix Controller: 80 GB PathPilot Console: 24 GB
Built-in Dropbox™ support for seamlessly transferring programs