

SPEC SHEET

xSTECH CNC ROUTER MILL

TORMACH.COM/XSTECH



The ideal machine for socially distant learning



TRAVELS

X-Axis	8.6 in. (220 mm)
Y-Axis	6.3 in. (160 mm)
Z-Axis	2.4 in. (61 mm)

SPINDLE

Spindle Power	120 W (0.12 kW) Brushless DC
Maximum Speed	20,000 RPM
Spindle Taper	ER11
Noise Level (No Load Operation)	<66 db[A]
Repositioning Accuracy	0.004 in (0.10 mm)

POWER

Power Required	Single-Phase, 50-60 Hz 120 Vac (USA/Canada, PN 39177) 230 Vac (International, PN 50614)
----------------	---

MACHINE SPECIFICATIONS

Table Size	12.6 in. x 5.9 in. (320 mm x 150 mm)
Typical System Footprint	15.4 in. x 15.7 in. (391 mm x 399 mm)
Overall System Height	16.7 in. (424 mm)
Typical System Weight	33 lb (14.9 kg)
Maximum Table Load Weight	6.6 lb (3 kg)

WARRANTY

1-Year Warranty against defects in material and workmanship.
--

HIGHLIGHTED FEATURES

Fully-Enclosed with Safety Door Switch
Tormach PathPilot® Control System with Keyboard, Mouse, Touchscreen, and Tormach Jog Shuttle
ER11 Collet Uses Popular 1/8 inch, 1/4 inch, 4 mm, or 6 mm Tool Shanks
Starter Tooling Set with WER Collets and End Mills
Integrated Tool Setter
Clamp Kit

MACHINE CONTROLLER

<p>POWERED BY</p> <p>A Better User Experience</p>	User-friendly design
	Support for up to 4-axis continuous machining
<p>PathPilot HUB is a browser-based, full-featured PathPilot simulator, producing usable G-Code.</p>	Intuitive conversational programming
	Usable G-Code Memory: Touchscreen Controller: 8 GB
	Built-in Dropbox™ support for seamlessly transferring programs